

Kompatibilität Kältemittel

Kältemittel	GWP*	Sicherheitsbereich	Kompatibel
R-125	3500	A1	✓
R-134a	1430	A1	✓
R-404A	3922	A1	✓
R-407A	2107	A1	✓
R-407C	1774	A1	✓
R-407F	1825	A1	✓
R-407H	1495	A1	✓
R-410A	2088	A1	✓
R-417A	2346	A1	✓
R-421A	2631	A1	✓
R-422B	2526	A1	✓
R-422D	2729	A1	✓
R-427A	2138	A1	✓
R-438A	2264	A1	✓
R-448A	1386	A1	✓
R-449A	1397	A1	✓
R-450A	601	A1	✓
R-452A	2140	A1	✓
R-452C	2220	A1	✓
R-507A	3985	A1	✓
R-513A	631	A1	✓
R-513B	596	A1	✓
R-718	0	A1	✓

Kältemittel	GWP*	Sicherheitsbereich	Kompatibel
R1234yf	4	A2L**	✓
R1234ze	7	A2L**	✓
R-32	675	A2L**	✓
R-444A	92	A2L**	✓
R-447A	582	A2L**	✓
R-447B	740	A2L**	✓
R-452B	698	A2L**	✓
R-454A	239	A2L**	✓
R-454B	466	A2L**	✓
R-454C	148	A2L**	✓
R-457A	139	A2L**	✓
R-459A	460	A2L**	✓
R-290	3	A3**	✓
R-600A	3	A3**	✓

Hinweis >B< MaxiPro ist nicht für die Verwendung mit Ammoniak (R717) zugelassen

GWP: Global warming potential [CO₂ = 1,0]

** Es liegt in der Verantwortung des Installateurs (Kältetechnikers) unterschiedliche Kältemitteln einzusetzen, die wie folgt klassifiziert sind: A2/A2L (entflammbare Kältemittel) und A3 (leicht entflammbare Kältemittel). Standards, örtliche Vorschriften und sonstige Verhaltensregeln sind einzuhalten.

Refrigerant Compatibility Table

Refrigerant	GWP*	Safety Group	Compatible
R-125	3500	A1	✓
R-134a	1430	A1	✓
R-404A	3922	A1	✓
R-407A	2107	A1	✓
R-407C	1774	A1	✓
R-407F	1825	A1	✓
R-407H	1495	A1	✓
R-410A	2088	A1	✓
R-417A	2346	A1	✓
R-421A	2631	A1	✓
R-422B	2526	A1	✓
R-422D	2729	A1	✓
R-427A	2138	A1	✓
R-438A	2264	A1	✓
R-448A	1386	A1	✓
R-449A	1397	A1	✓
R-450A	601	A1	✓
R-452A	2140	A1	✓
R-452C	2220	A1	✓
R-507A	3985	A1	✓
R-513A	631	A1	✓
R-513B	596	A1	✓
R-718	0	A1	✓

Refrigerant	GWP*	Safety Group	Compatible
R1234yf	4	A2L**	✓
R1234ze	7	A2L**	✓
R-32	675	A2L**	✓
R-444A	92	A2L**	✓
R-447A	582	A2L**	✓
R-447B	740	A2L**	✓
R-452B	698	A2L**	✓
R-454A	239	A2L**	✓
R-454B	466	A2L**	✓
R-454C	148	A2L**	✓
R-457A	139	A2L**	✓
R-459A	460	A2L**	✓
R-290	3	A3**	✓
R-600A	3	A3**	✓

Please note >B< MaxiPro is not approved for use with Ammonia (R717)

GWP: Global warming potential [CO₂ = 1,0]

** When using refrigerants classified A2L (lower flammability), A2 (flammable) and A3 (higher flammability) ensure that all appropriate Standards and all local rules & regulations are adhered to.